

CGRUNNER









POLAR WHITE









BYD SEAL Specifications

Overall Length (mm) 4,800 Overall Width (mm) 1,875 Overall Height (mm) 1,460 Wheel Track - Front / Rear (mm) 1,620/1,625 Wheel Base (mm) 2,920 Minimum Turning Radius (mm) 5.7 Ground Clearance Unladen (mm) 145 Front Trunk Capacity (L) 50 Rear Trunk Capacity (L) 400 Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetain Rear Drive All-Wheel Drive Front Motor Type / Squirriet cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Maximum Torque (N-m) / 310 Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-10	Dimensions	Extended Range	AWD
Overall Height (mm) 1,460 Wheel Track - Front / Rear (mm) 1,620/1,625 Wheelbase (mm) 2,920 Minimum Turning Radius (mm) 5.7 Ground Clearance Unladen (mm) 145 Front Trunk Capacity (L) 50 Rear Trunk Capacity (L) 400 Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Rear Drive All-Wheel Drive Front Motor Type / Squirrel cage induction eage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Power (kW) / 310 Rear Motor Maximum Torque (N-m) / 310 Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance 360 59 3.8	Overall Length (mm)	4,800	
Wheel Track - Front / Rear (mm) 1,620/1,625 Wheelbase (mm) 2,920 Minimum Turning Radius (mm) 5.7 Ground Clearance Unladen (mm) 145 Front Trunk Capacity (L) 50 Rear Trunk Capacity (L) 400 Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Rear Drive All-Wheel Drive Front Motor Maximum Power (kW) / Saguinet cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Power (kW) 230 390 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) 5.9 3.8 Electric Range: NEDC Combined Cycle (km) 570 520 Seating Capacity 5 80 Bat	Overall Width (mm)	1,875	
Wheelbase (mm) 2,920 Minimum Turning Radius (mm) 5.7 Ground Clearance Unladen (mm) 145 Front Trunk Capacity (L) 50 Rear Trunk Capacity (L) 400 Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Rear Drive All-Wheel Drive Squirrel cage induction asymmetric motors and the first of th	Overall Height (mm)	1,460	
Minimum Turning Radius (mm) 5.7 Ground Clearance Unladen (mm) 145 Front Trunk Capacity (L) 50 Rear Trunk Capacity (L) 400 Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Rear Drive All-Wheel Drive Front Motor Type / Squirret cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Type Permanent Magnet Synchronous Motor Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Forque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Power (kW) 230 390 Maximum Power (kW) 59 386 Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Wheel Track - Front / Rear (mm)	1,620/1,625	
Ground Clearance Unladen (mm) Front Trunk Capacity (L) Rear Trunk Capacity (L) Kerb Weight (kg) Gross Vehicle Mass (kg) Traction Motor Drivetrain Front Motor Type Front Motor Maximum Power (kW) Front Motor Maximum Torque (N-m) Rear Motor Maximum Power (kW) Rear Motor Maximum Power (kW) Rear Motor Maximum Torque (N-m) Sequince (N-m) Sequinc	Wheelbase (mm)	2,93	20
Front Trunk Capacity (L) Rear Trunk Capacity (L) Rear Trunk Capacity (L) Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Front Motor Type Front Motor Maximum Power (kW) Front Motor Maximum Torque (N-m) Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) Electric Range: NEDC Combined Cycle (km) Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Peront & Rear Front Disc Brake Ventilated & Drilled Ventilated & Fixed Fixed Fixed Fixed Fixed Fixed Fixed	Minimum Turning Radius (mm)	5.	7
Rear Trunk Capacity (L) Kerb Weight (kg) Cross Vehicle Mass (kg) Cross Mall-Wheel Drive All-Wheel Drive Alloy Alloy Alloy	Ground Clearance Unladen (mm)	14	5
Kerb Weight (kg) 2,055 2,185 Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Rear Drive All-Wheel Drive Front Motor Type / Squirrel Cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Power (kW) 230 360 Maximum Power (kW) 230 360 Maximum Power (kW) 230 360 Maximum Torque (N-m) 360 360 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) 5.9 3.8 Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Ventilated & Prince Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Front Trunk Capacity (L)	50)
Gross Vehicle Mass (kg) 2,501 2,631 Traction Motor Drivetrain Rear Drive All-Wheel Drive Front Motor Type / Squirrel cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) 5.9 3.8 Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Rear Trunk Capacity (L)	40	0
Traction Motor Drivetrain Rear Drive All-Wheel Drive Front Motor Type / Squirrel cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) Rear Motor Maximum Torque (N-m) Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) Electric Range: NEDC Combined Cycle (km) Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Pouble Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Ventilated Front Brake Caliper Fixed Fixed Fixed Fixed Fixed Wheel Type	Kerb Weight (kg)	2,055	2,185
Drivetrain Rear Drive All-Wheel Drive Front Motor Type / Squirrel cage induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance - - Acceleration 0-100km/h (s) 5.9 3.8 Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis - Front & Rear Front Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers - Front & Rear Front Brake Ventilated & Drilled	Gross Vehicle Mass (kg)	2,501	2,631
Front Motor Type / Squirrel cage Induction asynchronous motor Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) 5.9 3.8 Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Traction Motor		
Front Motor Maximum Power (kW) / 160 Front Motor Maximum Torque (N-m) / 310 Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) 230 230 Rear Motor Maximum Torque (N-m) 360 360 Maximum Power (kW) 230 390 Maximum Torque (N-m) 360 670 Performance Acceleration 0-100km/h (s) 5.9 3.8 Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Double Wishbone Rear Suspension Pouble Wishbone Rear Suspension Pouble Wishbone Rear Suspension Pouble Wishbone Rear Suspension Pouble Wishbone Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Ventilated & Ventilated & Prixed Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Drivetrain	Rear Drive	All-Wheel Drive
Front Motor Maximum Torque (N-m) Rear Motor Type Permanent Magnet Synchronous Motor Rear Motor Maximum Power (kW) Rear Motor Maximum Torque (N-m) Rear Motor Maximum Torque (N-m) Rear Motor Maximum Torque (N-m) Maximum Power (kW) Rear Motor Maximum Torque (N-m) Maximum Torque (N-m) Performance Acceleration 0-100km/h (s) Electric Range: NEDC Combined Cycle (km) Electric Range: WLTC Combined Cycle (km) Front Suspension Rear Suspension Rear Suspension Pouble Wishbone Rear Suspension Rear Suspension Pront Suspension Rear Suspension Rear Suspension Pront Suspension Rear Suspension Rear Suspension Front Suspension Rear Suspension Pouble Wishbone Rear Suspension Pront Suspension Rear Suspension Pouble Wishbone Rear Suspension Pouble Wishbone Rear Suspension Pront Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Ventilated & Drilled Front Brake Caliper Fixed Fixed Fixed Mloy Alloy	Front Motor Type	/	Squirrel cage induction asynchronous motor
Rear Motor TypePermanent Magnet Synchronous MotorRear Motor Maximum Power (kW)230230Rear Motor Maximum Torque (N-m)360360Maximum Power (kW)230390Maximum Torque (N-m)360670PerformanceAcceleration 0-100km/h (s)5.93.8Electric Range: NEDC Combined Cycle (km)650580Electric Range: WLTC Combined Cycle (km)570520Seating Capacity5Battery TypeBYD Blade BatteryBattery Capacity (kWh)82.56ChassisFront SuspensionMulti-LinkFrequency Selective Damping (FSD) Shock Absorbers—Front & RearFront Disc BrakeVentilated & DrilledVentilated & DrilledRear Disc BrakeVentilatedVentilatedFront Brake CaliperFixedFixedWheel TypeAlloyAlloy	Front Motor Maximum Power (kW)	/	160
Rear Motor Maximum Power (kW) Rear Motor Maximum Torque (N-m) Rear Motor Maximum Torque (N-m) Maximum Power (kW) Maximum Power (kW) Rear Motor Maximum Torque (N-m) Maximum Power (kW) Maximum Torque (N-m) Rear Motor Maximum Torque (N-m) Maximum Torque (N-m	Front Motor Maximum Torque (N-m)	/	310
Rear Motor Maximum Torque (N-m)360360Maximum Power (kW)230390Maximum Torque (N-m)360670PerformanceAcceleration 0-100km/h (s)5.93.8Electric Range: NEDC Combined Cycle (km)650580Electric Range: WLTC Combined Cycle (km)570520Seating Capacity58YD Blade BatteryBattery TypeBYD Blade BatteryBattery Capacity (kWh)82.56ChassisFront SuspensionDouble WishboneRear SuspensionMulti-LinkFrequency Selective Damping (FSD) Shock Absorbers—Front & RearFront Disc BrakeVentilated & DrilledVentilated & DrilledRear Disc BrakeVentilatedVentilatedFront Brake CaliperFixedFixedWheel TypeAlloyAlloy	Rear Motor Type	Permanent Magnet Synchronous Motor	
Maximum Power (kW)230390Maximum Torque (N-m)360670PerformanceAcceleration 0-100km/h (s)5.93.8Electric Range: NEDC Combined Cycle (km)650580Electric Range: WLTC Combined Cycle (km)570520Seating Capacity5Battery TypeBYD Blade BatteryBattery Capacity (kWh)82.56ChassisFront SuspensionDouble WishboneRear SuspensionMulti-LinkFrequency Selective Damping (FSD) Shock Absorbers—Front & RearFront Disc BrakeVentilated & DrilledVentilated & DrilledRear Disc BrakeVentilatedVentilatedFixedFront Brake CaliperFixedFixedWheel TypeAlloyAlloy	Rear Motor Maximum Power (kW)	230	230
Maximum Torque (N-m)360670PerformanceAcceleration 0-100km/h (s)5.93.8Electric Range: NEDC Combined Cycle (km)650580Electric Range: WLTC Combined Cycle (km)570520Seating Capacity5Battery TypeBYD Blade BatteryBattery Capacity (kWh)82.56ChassisFront SuspensionDouble WishboneRear SuspensionMulti-LinkFrequency Selective Damping (FSD) Shock Absorbers—Front & RearFront Disc BrakeVentilated & DrilledVentilated & DrilledRear Disc BrakeVentilatedVentilatedFront Brake CaliperFixedFixedWheel TypeAlloyAlloy	Rear Motor Maximum Torque (N-m)	360	360
Acceleration 0-100km/h (s) Acceleration 0-100km/h (s) Electric Range: NEDC Combined Cycle (km) Electric Range: WLTC Combined Cycle (km) Solution Solution Electric Range: WLTC Combined Cycle (km) Electric Range: WLTC Combined Cycle (km) Solution Seating Capacity Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Maximum Power (kW)	230	390
Acceleration 0-100km/h (s) Electric Range: NEDC Combined Cycle (km) Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Rear Suspension Rear Suspension Pouble Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Maximum Torque (N-m)	360	670
Electric Range: NEDC Combined Cycle (km) 650 580 Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Fixed Fixed Wheel Type Alloy Alloy	Performance		
Electric Range: WLTC Combined Cycle (km) 570 520 Seating Capacity 5 Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Acceleration 0-100km/h (s)	5.9	3.8
Seating Capacity Battery Type BYD Blade Battery Battery Capacity (kWh) 82.56 Chassis Front Suspension Rear Suspension Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Electric Range: NEDC Combined Cycle (km)	650	580
Battery Type Battery Capacity (kWh) Chassis Front Suspension Rear Suspension Rear Suspension Trequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type BYD Blade Battery 82.56 Double Wishbone Multi-Link Front & Rear Front & Rear Ventilated & Drilled Ventilated & Ventilated & Fixed Fixed Fixed Alloy Alloy	Electric Range: WLTC Combined Cycle (km)	570	520
Battery Capacity (kWh) Chassis Front Suspension Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Seating Capacity	5	
Chassis Front Suspension Double Wishbone Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Drilled Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Battery Type	BYD Blade Battery	
Front Suspension Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Ventilated Ventilated Ventilated Wheel Type Alloy Alloy	Battery Capacity (kWh)	82.56	
Rear Suspension Multi-Link Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Chassis		
Frequency Selective Damping (FSD) Shock Absorbers — Front & Rear Front Disc Brake Ventilated & Drilled Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Front Suspension	Double Wishbone	
Front Disc Brake Ventilated & Drilled Ventilated & Drilled Rear Disc Brake Ventilated Ventilated Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Rear Suspension	Multi-Link	
Rear Disc BrakeVentilatedVentilatedFront Brake CaliperFixedFixedWheel TypeAlloyAlloy	Frequency Selective Damping (FSD) Shock Absorbers	_	Front & Rear
Front Brake Caliper Fixed Fixed Wheel Type Alloy Alloy	Front Disc Brake	Ventilated & Drilled	Ventilated & Drilled
Wheel Type Alloy Alloy	Rear Disc Brake	Ventilated	Ventilated
, , ,	Front Brake Caliper	Fixed	Fixed
Tyre Size 235/45 P10 235/45 P10	Wheel Type	Alloy	Alloy
Tyre 5/20	Tyre Size	235/45 R19	235/45 R19

New Energy	EXTENDED RANGE	AWD
AC Charging Port - Type 2 (7kW)	•	•
Portable Charging Cable (mode 2)	0	0
DC Charging Port - CCS 2 (110kW)	_	_
DC Charging Port - CCS 2 (150kW)	•	•
V2L Function	•	•
V2L Discharge Adapter	0	0
Regenerative Braking	•	•
Safety and Security		
Front Airbags - Driver & Front Passenger	•	•
Side Airbags - Driver & Front Passenger	•	•
Side Curtain Airbags - Front & Rear	•	•
Far-side Airbags - Driver	•	•
Dual Stage Pretensioner On Front Seat Belts	•	•
Pretensioner On Rear Seat Belts	•	•
Seat Belt Reminder - Front & Rear	•	•
360° Camera	•	•
Front Parking Sensor (2 Zones)	•	•
Rear Parking Sensor (4 Zones)	•	•
ISOFIX Child Restraint Anchorage Points	•	•
Electronic Child Lock	_	•
Intelligent Power Brake System	•	•
Electric Power Steering (DP-EPS)	•	•
Hydraulic Brake Boost (HBB)	•	•
Hydraulic Brake Assist (HBA)	•	•
Traction Control System (TCS)	•	•
Controller Deceleration Parking (CDP)	•	•
Vehicle Dynamics Control (VDC)	•	•
Electronic Brake Force Distribution (EBD)	•	•
Hill Hold Control (HHC)	•	•
Auto-Hold	•	•
Adaptive Cruise Control (ACC)	•	•
Automatic Emergency Braking (AEB)	•	•
Lane Departure Warning (LDW)	•	•
Lane Departure Prevention (LDP)	•	•
Emergency Lane Keeping Assist (ELK)	•	•
Rear Collision Warning (RCW)	•	•
Intelligent Cruise Control (ICC)	•	•
Predictive Collision Warning (PCW)	•	•
Traffic Sign Recognition (TSR)	•	•
Intelligent Speed Limit Information (ISLI)	•	•
Intelligent Speed Limit Control (ISLC)	•	•
Front Cross Traffic Alert (FCTA)	•	•
Front Cross Traffic Brake (FCTB)	•	•
Rear Cross Traffic Alert (RCTA)	•	•
Rear Cross Traffic Brake (RCTB)	•	•
Blind Spot Detection (BSD)	•	•
Door Open Warning (DOW)	•	•
High Beam Assist (HMA)	•	•
Driver Attention Warning (DAW)	•	•
	•	-

Intelligence Torque Adaption Control (iTAC)	-	•
Exterior		
Silver-plated Panoramic Glass Roof	•	•
Electronic Hidden Door Handles	•	•
Rear Windscreen Mount Antenna	•	•
One-touch Open/Close Tailgate	•	•
Electrically Heated And Adjustable Exterior Mirrors	•	•
Electrically Retractable Exterior Mirrors	•	•
Door Mirror Auto-tilt	•	•
Door Mirror Position Memory	•	•
Auto Windows With Anti-trap	•	•
Soundproof Double Glazed Glass - Windshield And Front Door	•	•
Rear Windscreen With Electric Heating And Defrosting	•	•
Interior		
Steering Wheel Mounted Controls - Audio, Phone,	•	•
Acc And Multi-function Display		
Imitation Leather-wrapped Steering Wheel	_	_
Genuine Leather-wrapped Steering Wheel	•	•
10.25-inch Lcd Instrumentation	•	•
Centre Console Storage Compartment	•	•
Imitation Leather-wrapped Seats	_	_
Genuine Leather-wrapped Seats	•	•
Driver Seat 8-way Power Adjustable	•	•
Driver Seat 4-way Lumber Power Adjustment	•	•
Passenger Seat 6-way Power Adjustable	•	•
Front Seats Ventilated & Heated	•	•
Driver Seat With Position Memory	•	•
Courtesy Seating	•	•
Vice Dashboard With Dual Cup Holders	•	•
Front Height-Adjustable Cup Holder	•	•
Rear Row Central Armrest (With Dual Cup Holders)	•	•
Automatic Anti-dazzle Interior Rearview Mirror	•	•
Rain Sensing Frameless Wipers	•	•
Metal Doorsill Protectors	•	•
Front Sun Visor With Vanity Mirror & Lighting	•	•
Entertainment		
FM Radio	•	•
*Apple CarPlay® (USB) and Android Auto™ (wireless)	•	•
*Bluetooth® Phone Connectivity And Audio Streaming	•	•
15.6 Inch Intelligent Rotating Touch Screen Display	•	•
DYNAUDIO, 12 Speakers	•	•
Voice Assistant - English	•	•
1 x USB-C & 1 x USB-A, Front	•	•
1 x USB-C & 1 x USB-A, Rear	•	•
Light		
LED Headlight	•	•
Follow Me Home Headlight	•	•
Tottow me Home readilight		

Rear Fog Light	•	•
Sequential Rear Indicators	•	•
LED Centre High Mount Stop Light	•	•
RGB Dynamic Mood Lights With Rhythm Function	•	•
LED Front Reading Light	•	•
LED Rear Side Reading Light	•	•
Luggage Compartment Light	•	•
Comfort and Convenience		
Keyless Entry & Start	•	•
NFC Card Key	•	•
Wireless Phone Charger × 2	•	•
12V Accessory Socket	•	•
PM2.5 Filtration System	•	•
PM2.5 High Efficiency Filter (CN95)	•	•
Negative Ion Air Purifier	•	•
Automatic Dual-zone Heat Pump Air-conditioning	•	•
Rear Central Air Vents	•	•
Tyre Repair Kit	•	•
Tool Kit	•	•

- The real range is influenced by many factors such as individual driving style, load, traffic etc. The declared range is estimated for
- Bluetooth® is a registered trademark of Bluetooth SIG, Inc. Compatibility and functionality varies depending on device.
- Apple CarPlay® is a registered trade mark of Apple Inc. Requires compatible device, USB connection
- Android Auto™ is a registered trade mark of Google Inc. Requires compatible device and wireless Android Auto™ is compatible with an active data plan, 5 GHz Wi-Fi support and the latest version.
- Colours depicted are a guide only and may vary from actual colours due to the printing.
- Driving assist system are not a substitute for the driver's responsibility of the vehicle.
- BYD reserves the right to vary vehicle specifications and standard features from those detailed in this brochure.

Dimensions








Interior color









Test 2023



